

## ZQ-T8650



## ZQ-T8550



## ZQ-T8556



SPECIFICATION	ZQ-T8650	ZQ-T8550	ZQ-T8556
CPU	Intel Core i5 4210U, 1.7 GHz up to 2.7GHz	Intel Baytrail-D, Celeron J1900, 2.0GHz up to 2.41 GHz, TDP 10W	Intel Baytrail-D, Celeron J1900, 2.0GHz up to 2.41 GHz, TDP 10W
Graphics	Intel HD Graphics 4400	Intel HD Graphics	
Graphic Output	VGA, HDMI, LVDS, EDP	VGA, LVDS, EDP	
Display	15" TFT LCD, 1024 x 768 (max.)		15.6" TFT LCD, 1920 x 1080 (max)
Viewing Angle	45 degree adjustable		
Touch Solution	15" Capacitive touch panel		15.6" Capacitive touch panel
RAM	DDR3L 1333/1600MHz, 4GB as standard, optional up to 8 GB		
Storage	64 GB SSD as standard optional up to 256GB, 1 x SATA, 1 x M-SATA		
Audio	Realtek ALC 662HD (on board)		
LAN	Realtek RTL8111H, 1000m (on board)	Realtek RTL8106E-CG (on board)	
Extended Slots	1 x MINI-PCIE (for 4G/WIFI), 1 x SIM (on board)	1 x MINI-PCIE (for 4G/WIFI), 1 x Micro-SIM (on board)	
Customer Display	VFD or 9.7" secondary monitor (option)		VFD or 13.3" secondary monitor (option)
I/O Ports	2 x USB 3.0 6 x USB 2.0 1 x LAN 1 x VGA 1 x HDMI 1 x MIC-IN, 1 x LINE-OUT 1 x DC12V_OUT 2 x RS232	1 x DC24V_IN, 1 x DC12V_OUT 1 x RJ11 for cash box 3 x RJ48 for RS232 4 x USB 2.0 + 1 x USB 2.0 1 x RJ45 for LAN 1 x VGA 1 x LINE -OUT	1 x DC24V_IN, 1 x DC12V_OUT 1 x RJ11 for cash box 3 x RJ48 for RS232 4 x USB 2.0 + 1 x USB 2.0 1 x RJ45 for LAN 1 x VGA 1 x LINE -OUT
O.S. Compliant	Windows 8, Windows 10, Linux (not included)		
Input Power	Ø 2.5 x DC 1V	DC24V	
Power Supply	100 ~ 240V / 47 ~ 63Hz	100 ~ 240V / 47 ~ 63Hz	
Work Environment	-10 ~ 60 degrees, 0% ~ 95%		

