

## Features

- Multi-touch capacitive screen
- Alloy metal housing design
- Unique streamline appearance
- Slim body with powerful functions
- Multiple configurations available



## Specification

<b>CPU</b>	J6412, Celeron quad-core quad-threads 2.0GHz
<b>Memory + Storage</b>	Standard 4G+64G, optional 8G+128/8G+256G
<b>Primary Display</b>	Size: 15.6 inch Resolution: 1920*1080 Type: TFT-LCD
<b>Sub-display (Optional)</b>	Size: 15.6 inch Resolution: 1920*1080 Type: TFT-LCD
<b>Touch Screen</b>	Type: Capacitive Interface: USB Touch points: default 3 points
<b>Printer (optional)</b>	<p>Print type: 58mm thermal dot line printer</p> <p>Print speed: Maximum 90mm/s</p> <p>Print width: 48mm</p> <p>Paper roll type: 57.5 ± 0.5mm, maximum outside diameter: 50mm</p> <p>Paper cutting method: manual tearing paper</p> <p>Support barcode: JAN13 (EAN13), JAN8 (EAN8), CODE39, CODE128, QR</p> <p>Life span: 100,000,000 pulses or more, more than 50 kilometers</p> <p>Interface type: USB</p>
<b>MSR (optional)</b>	<p>Channel position: ISO1 (1ATA), ISO2 (ABA), ISO3 (MINTS)</p> <p>Recording density: 210BPI, 75BPI, 210BPI</p> <p>Recording character count: 79 characters, 40 characters, 107 characters</p> <p>Operation speed: 10cm/sec ~ 150cm/sec</p> <p>Decoding method: F/2F</p> <p>Card standard: ISO 7811/7812</p> <p>Card thickness: PVC 0.76 ± 0.08mm</p> <p>Magnetic head life: 500,000 times (1 time: swipe the card once)</p>